



Confine Series

Recessed
Groundlight



Confine Series is available as a linear recessed ground light in several lengths and 2 widths.

Construction: Extruded aluminium with tempered glass and stainless steel trim. IP68. IK10.

Lens: Clear 8mm tempered Glass.

Installation: Separate Installation Cassette supplied with Luminaire. 300mm drainage area needed. Surface Temperature to 70°C.

Finish: Brushed stainless steel.

LED: 9w - 36w LEDs. Symmetric. 4K as standard (3K on request).


Options: RGB, T5, Wall Versions, Asymmetric Versions, Dali.

Manufactured: EU.

Product Compliance: EN 60598; CE.

Warning: Groundlite can be glare , slip or burn hazard. Vandalism or accidental breakage can result in electrical, glass or trip hazard. Locate to avoid or minimise these hazards.

DIMENSIONS



All Dimensions in mm. * Note Cassette will add 43mm to lengths above.

Dimensions (in mm.)	Size 1	Size 2	Size 3	Size 4
A (length) *	375	635	930	1230
B (visable width)	125	125	125	125
C (depth)	100	100	100	100
D (hidden width)	140	140	140	140



ORDERING CODE

Wattage	Type	Size	Code	Details	+ Cassette	Lumens*
9w	LED	1	G1295.LVMT400	Confine, 4K, Symmetric Beam 25°	GAC280	972 lm
18w	LED	2	G1296.BUMT400	Confine, 4K, Symmetric Beam 25°	GAC281	1944 lm
27w	LED	3	G1297.ELMT400	Confine, 4K, Symmetric Beam 25°	GAC282	2916 lm
36w	LED	4	G1298.ENMT400	Confine, 4K, Symmetric Beam 25°	GAC283	3888 lm

*Source lumens

OPTIONS

RGB: RGB on request