




## Tube

### LED Tubular Light



Tube is suitable for Industrial and Food Processing environments.

**Construction:** Anti-corrosive clear Acrylic housing as standard with option for Polycarbonate (IK10). Frosted Tube on request. IP69K.  
Pendant Version as standard. Surface Mounted on request.

**Lens:** Clear tempered glass as standard. Other types on request.

**Finish:** Clear Lens as standard. Surface Mounted on request.

**LED:** 20w-50w LED. 4K as standard.  
Rated Life: 50,000 hrs.

**Optics:** 120° Medium Beam as standard. Narrow 60° beam on request.  
Glare UGR<19.

**Options:** Beam angles, Clear/Frosted Lens, PC or PMMA, Surface Mounted.

**Product Compliance:** EN 60598; CE.



Surface Mounted Version

### ORDERING CODE

Wattage	Type	Code	Description	Dimensions	Lumens
20w	LED	3TBS00020	Tubular Pendant Light, Clear Acrylic, 120° 4k	120 x 84 x 600mm	2600 lm
40w	LED	3TBS00040	Tubular Pendant Light, Clear Acrylic, 120° 4k	120 x 84 x 1128mm	5200 lm
50w	LED	3TBS00050	Tubular Pendant Light, Clear Acrylic, 120° 4k	120 x 84 x 1390mm	6500 lm

### OPTIONS

60: Narrow Beam Angle
PC: Polycarbonate
SM: Surface Mounted Version
FR: Frosted Lens