



Softbay LED

Internal Lighting



Ideal for efficient commercial and Industrial lighting. Optional Reflectors or Prismatic Refractor. The refractor is visually attractive, low glare and the uplight element eliminates ceiling darkness.

Construction: Die cast aluminium, glass lens with polycarbonate refractor. IP65.

Finish: White as standard.

LED: 100w, 150w or 200w LED. Nichia. 4000K as standard. 5000K on request. Ambient temperature: +40°C to -40°C.

LED Life: L70 >50,000 hours.

Options: 1-10V, Dali, 3K/5K, Reflectors.

Product Compliance: EN 60598; CE.



DIMENSIONS

	70°	60°	90°	No Reflector
Diameter	412	360	360	300
Height	477	362	362	212
Weight: 8 Kgs		All dimensions in mm.		

ORDERING CODE - 70° PRISMATIC REFRACTOR

Code	Wattage	Description	Lumens
3SBL12LBA	100w	LED SoftBay with 70° Prismatic Refractor	12380 lm
3SBL13LBA	150w	LED SoftBay with 70° Prismatic Refractor	18630 lm
3SBL14LBA	200w	LED SoftBay with 70° Prismatic Refractor	24330 lm

ORDERING CODE - ALUMINIUM 60° REFLECTOR

3SBL12LBB	100w	LED HighBay with 60° Aluminium Reflector	12180 lm
3SBL13LBB	150w	LED HighBay with 60° Aluminium Reflector	18380 lm
3SBL14LBB	200w	LED HighBay with 60° Aluminium Reflector	24190 lm

ORDERING CODE - ALUMINIUM 90° REFLECTOR

3SBL12LBC	100w	LED HighBay with 90° Aluminium Reflector	12280 lm
3SBL13LBC	150w	LED HighBay with 90° Aluminium Reflector	18700 lm
3SBL14LBC	200w	LED HighBay with 90° Aluminium Reflector	24300 lm

OPTIONS

5K: 5000K
3K: 3000K
DIM: 1-10V Dimming